


Teagle

TOMAHAWK 9500

Bale Processor



HIGH PERFORMANCE • FEEDING • BEDDING

TOMAHAWK 9500

Our latest 'wide body' design

- Greater capacity, easier loading
- Increased output and delivery
- Compact and manoeuvrable
- Hardened Steel fan housing



FEEDS

Clamp/Chopped Silage

SPREADS

Straw up to 72ft

CAPACITY

230 Bushel

Features/Options



1 Wireless control

Slimline control panel uses Bluetooth® wireless technology for straight-forward communication between the operator and the Tomahawk 9500.



2 Twin crossbeaters

For a high and consistent discharge rate, ideally suited for feeding clamp materials, chopped bale silage and spreading straw.



3 Superior performance

Wide body format delivers greater capacity, increased throughput and delivery distance from the large diameter fan. Hardox housing as standard



4 Driver pack

Lights, mudguards and remote tailgate switch are fitted as standard.

Front cover image shows optional braked axle (385/55 R22 tyres) & tailgate extension.

“Compact performance for feeding & bedding”

Ben Bennett runs the family farm near Stoke Climsland, his focus being a beef fattening operation that works in batches of 100 Friesian/Holstein calves located across 2 sites.

The farm is based on 150 acres, mainly set to arable and maize, with additional barley and straw purchased for feeding and bedding.



“Accurately managing costs”.

When looking for a dual purpose feeder/bedder Ben specifically wanted a weigh cell system so that he could accurately weigh in and weigh out to monitor inputs. This enables him to calculate cost of production and feed conversion rates.

“We needed a compact machine to get around the tighter yards. The 9500 is manoeuvrable, but still has a large capacity, and with the weigh system and its ability to recirculate for mixing feed, the machine meets all of our requirements.”

“Jumping in a pen with 20 bulls is not my idea of good morning exercise”.

Prior to the Tomahawk being purchased the bull calves were bedded manually with straw, feed being dispensed with a bucket and top dressed with corn and protein. Ben was keen to make the feeding and bedding operations more efficient as each was consuming a lot of time. In addition safety was a concern, Ben noting that “jumping in a pen with 20 bulls is not my idea of good morning exercise”.

The benefits of the Tomahawk 9500 have been clear.

“We were previously spending 2 hours a day bedding 6 bales (8x4x3 bales) by hand which now takes 40 minutes. We are also saving around 20% in straw, or around 1 bale/day.” For feeding, “we make use of the large capacity of the 9500 to load around 2.5 tonnes of feed. The ration contains around 50% maize, 40% barley and 10% minerals and protein. To ensure that the mix is consistent we run the machine with the chute ‘recirculating’ the feed for around 5 minutes, or one complete recirculation of the mix, after loading”.



1 Weigh system

3 point weigh system for accurate and instantaneous measurement (optional extra). Programmable controller for management of rations and measurement of delivery.



2 Side discharge chute

Ideal where discharge height is limited, or additional blow distance is required. Chute can be raised or lowered from the cab as required.



3 Tailgate extension

Increase capacity and ease of loading, attaches easily to a standard tailgate. (optional extra)



4 Other accessories

- Wide angle joint PTO
- Swivel chute extension
- Greedy boards
- Braked Axle

Specifications



	9500 Side Chute	9500 Swivel Chute
Capacity	230 Bushel	230 Bushel
Blow Distance	82ft	72ft
Beaters	2	2
Clamp or Chopped Bale Silage	Yes	Yes
Baled Silage (unchopped)	No	No
Baled Straw	Yes	Yes
No. of round bales	3 x 5'x5' Bales or 2 x 6'x5' Bales	
No. of rectangular bales	2 x (8'x4'x3') or 1 x (8'x4'x4')	
Bale chamber (tailgate down)	13ft(L) x 5ft.6in(W) x 5ft.1in(H)	
Length (tailgate up/down)	17ft/20ft.9in	17ft/20ft.9in
Width (transport/operation)	8ft.2in/10ft4in	7ft.3in/7ft.3in
Height (transport/operation)	9ft.6in/9ft.6in	9ft.6in/11ft.7in
Tyre size (standard)	305/55R 22	305/55R 22
Weight (standard axle)	6629lbs	6651lbs
Min tractor size	60kW/80HP	60kW/80HP

Dealer

Importer

The company's policy is one of continuous improvement and development, therefore specifications are subject to change without prior notice.

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Teagle Machinery Ltd is under license. Other trademarks and trade names are those of their respective owners.

North America Sales Manager

Andy Robson 252 292 0911

Toll Free: 1-855-383-2453 1-855-3TEAGLE

Teagle Machinery Ltd, PO Box 3347, Wilson, NC 27895, USA

salesna@teagle.co.uk www.teaglemachinery.com



Teagle
we're right behind you

Teagle Machinery Ltd, Blackwater, Truro, Cornwall, England, TR4 8HQ



TOM95000580AE US